

T6218 Product Datasheet



Type: Wall Light
 Material: Plaster
 Dimensions: H:75mm W:390 D:200
 Earth Class: CE Class 1
 IP Rating: IP20
 Bathroom Zone: Zone 3
 Paintable: Yes
 F Mark: No

Light Source Options:

| Order Code | Lamp Type | Lamp Included | Max Wattage | Lumen Output | Colour Temp. | CRI | Dimmable | Dimming Method | Voltage/Freq. |
|------------|------------------|---------------|-------------|--------------|--------------|-------|----------|--------------------------------|-----------------|
| T6218/R7s | Tungsten Halogen | No | 100w | 1600lm* | 2700k* | 80ra* | Yes | Rheostat (Lamp Dependant) | 240v 50/60hz |
| T6218/10 | LED | Yes | 10w | 1200lm | 2700k | 80ra | No | N/A | 240v 50/60hz |
| T6218/15D | LED | Yes | 15w | 2000lm | 2700k | 80ra | Yes | Varilight V-Pro LED or Similar | 240v 50/60hz |

* Typical values, dependent on lamp.

Emergency Pack Options:

Emergency pack must be specified if required.

| Type | Power Rating Non Maintained | Power Rating Maintained | Emergency Duration | Battery Type | Recharge Time | Output Load | Dedicated Led | Component Manufacturer(s) |
|----------------|-----------------------------|-------------------------|--------------------|---|---------------|-------------|---------------|---------------------------|
| Emergency Pack | 1.8w | 3.7w | 3 Hours | Lithium-ion or LiFePO4 (dependent on luminaire size) - Max ambient temp. 35°C | 24 Hours | 1.0w | Yes | |

Technical Drawing:

