

TC9455 Product Datasheet



Type: Wall Light
 Material: Concrete
 Dimensions: H:70mm W:300 D:70
 Earth Class: CE Class 1
 IP Rating: IP20
 Bathroom Zone: Zone 3
 Paintable: Yes
 F Mark: No

A contemporary concrete up/down light, featuring a discrete 70mm front profile height. Suitable for wall mounting.

[Click for more info online](#)

Light Source Options:

Order Code	Lamp Type	Lamp Included	Max Wattage	Lumen Output	Colour Temp.	CRI	Dimmable	Dimming Method	Voltage/Freq.
TC9455 /R7s	Tungsten Halogen	No	100w	1600lm*	2700k*	80ra*	Yes	Rheostat (Lamp Dependant)	240v 50/60hz
TC9455 /10	LED	Yes	10w	1200lm	2700k	80ra	No	N/A	240v 50/60hz
TC9455 /15D	LED	Yes	15w	2000lm	2700k	80ra	Yes	Varilight V-Pro LED or Similar	240v 50/60hz

* Typical values, dependent on lamp.

Emergency Pack Options:

Emergency pack must be specified if required.

Type	Power Rating Non Maintained	Power Rating Maintained	Emergency Duration	Battery Type	Recharge Time	Output Load	Dedicated Led	Component Manufacturer(s)
Emergency Pack	1.8w	3.7w	3 Hours	Lithium-ion or LiFePO4 (dependent on luminaire size) - Max ambient temp. 35°C	24 Hours	1.0w	Yes	

Technical Drawing:

