

## TR8280 Product Datasheet



Type: Wall Light  
 Material: Plaster  
 Dimensions: H:250mm W:150 D:150  
 Earth Class: CE Class 1  
 IP Rating: IP20  
 Bathroom Zone: Zone 3  
 Paintable: Yes  
 F Mark: No

A compact cuboid up/down light, with a projection of just 150mm, making it ideally suited to smaller rooms and spaces. See also our style matched TR8180 fitting which has the same cross sectional dimensions.

[Click for more info online](#)

### Light Source Options:

Order Code	Lamp Type	Lamp Included	Max Wattage	Lumen Output	Colour Temp.	CRI	Dimmable	Dimming Method	Voltage/Freq.
TR8280 /GU10	LED	No	7w	440lm*	2700k*	80ra*	Yes	Rheostat (Lamp Dependant)	240v 50/60hz
TR8280 /10	LED	Yes	10w	1200lm	2700k	80ra	No	N/A	240v 50/60hz
TR8280 /14D	LED	Yes	14w	760lm	2700k	80ra	Yes	Varilight V-Pro LED or Similar	240v 50/60hz

\* Typical values, dependent on lamp.

### Emergency Pack Options:

Emergency pack must be specified if required.

Type	Power Rating Non Maintained	Power Rating Maintained	Emergency Duration	Battery Type	Recharge Time	Output Load	Dedicated Led	Component Manufacturer(s)
Emergency Pack	1.8w	3.7w	3 Hours	Lithium-ion or LiFePO4 (dependent on luminaire size) - Max ambient temp. 35°C	24 Hours	1.0w	Yes	

### Technical Drawing:

