

TR7226 Product Datasheet



Type: Wall Light
 Material: Plaster
 Dimensions: H:350mm W:250 D:75
 Earth Class: CE Class 1
 IP Rating: IP20
 Bathroom Zone: Zone 3
 Paintable: Yes
 F Mark: No

The TR7226 is a slim up/down light with a shallow projection of just 75mm from the wall. This light works well in medium to large rooms and spaces, and is ideally suited to use in bedrooms and stairwells, where a slim projection is desirable.

[Click for more info online](#)

Light Source Options:

Order Code	Lamp Type	Lamp Included	Max Wattage	Lumen Output	Colour Temp.	CRI	Dimmable	Dimming Method	Voltage/Freq.
TR7226 /20	LED	Yes	20w	2400lm	2700k	80ra	No	N/A	240v 50/60hz
TR7226 /30D	LED	Yes	30w	4000lm	2700k	80ra	Yes	Varilight V-Pro LED or Similar	240v 50/60hz
TR7226 /12	LED	Yes	12w	940lm	2700k	80ra	No	N/A	240v 50/60hz

Emergency Pack Options:

Emergency pack must be specified if required.

Type	Power Rating Non Maintained	Power Rating Maintained	Emergency Duration	Battery Type	Recharge Time	Output Load	Dedicated Led	Component Manufacturer(s)
Emergency Pack	1.8w	3.7w	3 Hours	Lithium-ion or LiFePO4 (dependent on luminaire size) - Max ambient temp. 35°C	24 Hours	1.0w	Yes	

Technical Drawing:

