

TR8281 Product Datasheet



Type: Wall Light
 Material: Plaster
 Dimensions: H:16mm W:305 D:110
 Earth Class: CE Class 1
 IP Rating: IP20
 Bathroom Zone: Zone 3
 Paintable: Yes
 F Mark: No

The TR8281 is a plaster up/down light. This light works well in medium to large rooms and spaces. This timeless fitting was one of the first in our linear range and features balanced proportions with a 110mm projection from the wall. See also our TR9281, a similar fitting with an even slimmer projection.

[Click for more info online](#)

Light Source Options:

Order Code	Lamp Type	Lamp Included	Max Wattage	Lumen Output	Colour Temp.	CRI	Dimmable	Dimming Method	Voltage/Freq.
TR8281 /E27	Tungsten Halogen	No	60w	660lm*	2700k*	80ra*	Yes	Rheostat (Lamp Dependant)	240v 50/60hz
TR8281 /20	LED	Yes	20w	2400lm	2700k	80ra	No	N/A	240v 50/60hz
TR8281 /30D	LED	Yes	30w	4000lm	2700k	80ra	Yes	Varilight V-Pro LED or Similar	240v 50/60hz

* Typical values, dependent on lamp.

Emergency Pack Options:

Emergency pack must be specified if required.

Type	Power Rating Non Maintained	Power Rating Maintained	Emergency Duration	Battery Type	Recharge Time	Output Load	Dedicated Led	Component Manufacturer(s)
Emergency Pack	1.8w	3.7w	3 Hours	Lithium-ion or LiFePO4 (dependent on luminaire size) - Max ambient temp. 35°C	24 Hours	1.0w	Yes	

Technical Drawing:

