

TR9155 Product Datasheet



Type: Wall Light
Material: Plaster
Dimensions: H:70mm W:600 D:140
Earth Class: CE Class 1
IP Rating: IP20
Bathroom Zone: Zone 3
Paintable: Yes
F Mark: No

A long, slim plaster wall uplight designed to provide huge amounts of light output whilst maintaining a discrete low profile. It's slim projection is just 140mm from the wall, and only 70mm in height. The fitting works well in larger spaces and long corridors. See also our style matched TR9055 up/down light.

[Click for more info online](#)

Light Source Options:

Order Code	Lamp Type	Lamp Included	Max Wattage	Lumen Output	Colour Temp.	CRI	Dimmable	Dimming Method	Voltage/Freq.
TR9155 /20DALI	LED	Yes	20w	1250lm	2700k	80ra	Yes	DALI	240v 50/60hz

Emergency Pack Options:

Emergency pack must be specified if required.

Type	Power Rating Non Maintained	Power Rating Maintained	Emergency Duration	Battery Type	Recharge Time	Output Load	Dedicated Led	Component Manufacturer(s)
Emergency Pack	1.8w	3.7w	3 Hours	Lithium-ion or LiFePO4 (dependent on luminaire size) - Max ambient temp. 35°C	24 Hours	1.0w	Yes	

Technical Drawing:

