

TR9281 Product Datasheet



Type: Wall Light
 Material: Plaster
 Dimensions: H:175mm W: 330mm D: 75mm
 Earth Class: CE Class 1
 IP Rating: IP20
 Bathroom Zone: Zone 3
 Paintable: Yes
 F Mark: No

The TR9281 is a slim and compact up and down light with a shallow projection of just 75mm from the wall. It features frosted diffusers, both on top and bottom of the light, obscuring the light's innards, whilst allowing efficient convection cooling via the small slits on the upper diffuser. This light works well in medium to large rooms and spaces, and is ideally suited to use in bedrooms and stairwells, where a slim projection is desirable.

[Click for more info online](#)

Light Source Options:

Order Code	Lamp Type	Lamp Included	Max Wattage	Lumen Output	Colour Temp.	CRI	Dimmable	Dimming Method	Voltage/Freq.
TR9281 /E27	Tungsten Halogen	No	60w	660lm*	2700k*	80ra*	Yes	Rheostat (Lamp Dependant)	240v 50/60hz
TR9281 /20	LED	Yes	20w	2400lm	2700k	80ra	No	N/A	240v 50/60hz
TR9281 /30D	LED	Yes	30w	4000lm	2700k	80ra	Yes	Varilight V-Pro LED or Similar	240v 50/60hz

* Typical values, dependent on lamp.

Emergency Pack Options:

Emergency pack must be specified if required.

Type	Power Rating Non Maintained	Power Rating Maintained	Emergency Duration	Battery Type	Recharge Time	Output Load	Dedicated Led	Component Manufacturer(s)
Emergency Pack	1.8w	3.7w	3 Hours	Lithium-ion or LiFePO4 (dependent on luminaire size) - Max ambient temp. 35°C	24 Hours	1.0w	Yes	

Technical Drawing:

